

Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

Notes: \_\_\_\_\_

## LL52120-3-27K-GR **DISCONTINUED 01/13/2023** LL52130-3-30K-GR

### 7 Watt 3" Gimbal Recessed LED Downlight

**Housing/Finish:** Aluminum Construction with White Finish and Frosted Polycarbonate Lens. Junction Box and Driver Connect Included.

**Dimensions:**

- **LL52120-3-27K-GR:** 3.375"OD x 1.83"L
- **LL52130-3-30K-GR:** 3.375"OD x 1.83"L

**Light Source:**

- **LL52120-3-27K-GR:** 120V/7W/610lm Delivered@27k/80CRI.
- **LL52130-3-30K-GR:** 120V/7W/610lm Delivered@30k/80CRI.

**Notes:**

- 40° Beam Spread
- Gimbal ring rotates 360 degrees and angles up to 30 degrees
- Includes 26" of Feed Wire Between Light and External Driver

Provides Flexible Driver Positioning

- Fully Dimmable- Instant on:Compatible with most Dimmers
  - o **Leviton:** 011-IPL06-10Z, 012-TSL06-1LW, 001-RDL06-10Z, 011-IPL06-10Z, 12-TSL06-1LW, 001-RDL06-10Z, 001-RNL06-10Z, 6674-10W, 001-DW6HD-1BZ, 001-DW1KD-1BZ, 001-DSL06-1LZ, 6631, 6633-P, 6672, 6674
  - o **Lutron:** CTCL-153P, MACL-153M, DVCL-153P, LGCL-153P, TGCL-153P, SCL-153P, S-600, S-600P, DVCLV-300P, CT-103P, DV-600P, S2-L, TG-600P
  - o **Cooper:** DI06P



LL52120-3-27K-GR



LL52130-3-30K-GR

**Warranty:**

- 5 Year Limited Warranty
- 50K Life Hours
- cETLus Rated
- Damp Location Rated
- RoHS Compliant
- Energy Star Rated
- IC Rated



<b>MODEL</b>
LL52120-3-27K-GR LL52130-3-30K-GR

Not recommended for use with motion sensors, light sensors, timers or any other external controls. May be available with other voltage, wattage, finish, and cable length options by special order. Please contact your Lumencia Representative for more information