

Job Name: _____

Type: _____

Part #: _____

Notes: _____

DISCONTINUED 01/13/2023

LL52140-4-27K-GR LL52150-4-30K-GR 12 Watt 4" Gimbal Recessed LED Downlight

Housing/Finish: Aluminum Construction with White Finish and Frosted Polycarbonate Lens. Junction Box and Driver Connect Included.

Dimensions:

- LL52140-4-27K-GR: 5.04"OD x 2.24"L
- LL52150-4-30K-GR: 5.04"OD x 2.24"L

Light Source:

- LL52140-4-27K-GR: 120V/12W/850lm Delivered@27k/90CRI.
- LL52150-4-30K-GR: 120V/12W/850lm Delivered@30k/90CRI.



Notes:

- Gimbal ring rotates 360 degrees and angles up to 30 degrees
- 40° Beam Spread
- Includes 26" of Feed Wire Between Light and External Driver

Provides Flexible Driver Positioning

- Fully Dimmable- Instant on: Compatible with most Dimmers
 - o Leviton: 6631, 6633-P, 6672, 6674
 - o Lutron: CTCL-153P, MACL-153M, DVCL-153P, LGCL-153P, TGCL-153P, SCL-153P, S-600, S-600P, DVCLV-300P, CT-103P, DV-600P, S2-L, TG-600P
 - o Cooper: DIO6P

Warranty:

- 5 Year Limited Warranty
- 50K Life Hours
- cETLus Rated
- Damp Location Rated (Indoor Use Only)
- RoHS Compliant
- Energy Star Rated
- IC Rated
- Can be used to comply with the 2019 Title 24, Part 6 high efficacy light source requirements in the state of California.



MODEL
LL52140-4-27K-GR LL52150-4-30K-GR

Not recommended for use with motion sensors, light sensors, timers or any other external controls. May be available with other voltage, wattage, finish, and cable length options by special order. Please contact your Lumencia Representative for more information